## HORIZONTAL SHAPER MACHINE





## Specification of Cone Pulley Belt and All Geared Shaper Machine

MODEL	DHS - 12	DHS - 18	DHS - 24	DHS - 30
RAM				
Length of Ram Stroke	12" / 305mm	18"/ 457mm	24"/610mm	30"/762mm
Length of Ram	26" / 660mm	40.5" /1029mm	50"/1270mm	58"/1473mm
Length & Width of Ram Bearing	26 X 7"/660 X 178mm	28.5" X 9"/724 X 229mm	33 X 11.5"/838 X 292mm	39 x 13.5" /990 x 317mm
Max & Min Distance from Table to Ram	10X 1"/254 X25 mm	15 X 1"/381 X 26mm	18 X 3"/457 X 89mm	19 x 3"/483 x 76mm
TABLE				
Working Surface Of Table	12 x 8"/305 x 203mm	18 X 11.5 "/457 X 292mm	24 X 14"/610 X 356mm	30 x 15"/762 x 361mm
Max Table Travel Horizontal	16.5 */419 mm	18"/457mm	24"/610mm	30"/762mm
Max Table Travel Vertical	9"/ 229 mm	13"/330mm	15"/381mm	17.5 "/444mm
Angular Movement Of Table	60°L 60°R	60°L 60°R	60°L 60°R	60°L 60°R
BASE				
Length & Width Of Base	37 X 18"/940 X457mm	50X 17.5"/1270X 444mm	64 X 23"/1626 X 585mm	72 X 26"/ 1880 X 660mm
Length Of Main Slide Base	23" / 584mm	29"/736mm	36"/914mm	41"/2565mm
TOOL HEAD				
Max. Vertical Travel Of Tool Slide	5" / 127mm	5.5 "/139mm	5.5 "/146mm	5.5 "/146mm
Max.Swivel Of Tool Head	60'L 60'R	60L' 60'R	60°L 60°R	60°L 60°R
SPEED & FEEDS				
Range Of Ram Speed In Cone Pulley		3	4	3
Range OF Ram Speed In All Geared		4	4	4
Die Of Clutch Pulley	9.5" / 241mm	12"/305mm	12"/305mm	14"/355mm
Die Of Motor Pulley	2.5 " / 64mm	2 3/4"/70mm	2 3/4"/70mm	2 3/4"/70mm
Stroke Per Minutes	30,60,90	16,32,64,96	12,24,48,72	8,16,32,48
Range Of Table Feed Per Stroke Of Ram	0.009"/0.229mm	0.009"/0.229mm	0.009"/0.229mm	0.009"/0.229mm
Range Of Tool Head Feed	Hand Feed	Hand Feed	Hand Feed	Hand Feed
SPECIFICATION OF VICE	5"/127mm	8"/203mm	12"/304mm	131/2"/336mm
OVERALL DIMENSIONS & WEIGHT				
Length	48"/1219mm	62"/1580mm	78"/1981mm	88"/2150mm
Width	30"/762mm	37"/940mm	43"/1092mm	48"/1219mm
Heigh	54"/1371mm	55"/1400mm	63"/1600mm	62"/1550mm